GRYFFIN
HIGH SECURITY FENCING & GATES
Smarter solutions, guaranteed.

PRODUCT SPECIFICATION – "CLG400" - CANTILEVER GATE

PROPRIETARY SPECIFICATION

"CLG400" cantilever gate as manufactured by Gryffin High Security Fencing and Gates

SUB FRAME

Gate structure shall be manufactured using pre-galvanised steel SHS / RHS sections

GATE INFILL

Infill shall be typically vertical bar utilising 25mm SHS.

TRACK DETAIL

200mm Cantilever Track

AUTOMATION

Automation is provided via high duty electro-mechanical gate operator.

Gryffin safety supplied as standard with inbuilt obstacle detection, dual height and dual side photo-electrical beams, flashing light and warning sign.

FINISH OPTIONS:

- Galvabond steel (standard)
- Dulux Duralloy or Interpon D100 powdercoat finish
- Electro – static twin coat wet sprayed paint.

SPECIAL NOTES:

- The power supply required for the motor is either:
  - Single phase hard wired (10 amp), located within one metre of the motor.
  - Low voltage 24v wired supply, within one metre of the motor.
  - 24v High efficiency solar power.

Gryffin High Security Fencing and Gates has continuous program of product development, and reserve the right to change specifications at any time without notice